# JCAT

# Alternative Coatings for Fasteners on USMC-Expeditionary Fighting Vehicle

January 26, 2006
Hilton San Diego Resort
1775 East Mission Bay Drive
San Diego, CA 92109



maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collections this burden, to Washington Headquuld be aware that notwithstanding and DMB control number.	ion of information. Send comments arters Services, Directorate for Info	regarding this burden estimate or formation Operations and Reports	or any other aspect of the property of the contract of the con	nis collection of information, Highway, Suite 1204, Arlington
1. REPORT DATE 26 JAN 2006	2. DEPODE TYPE			3. DATES COVERED <b>00-00-2006 to 00-00-2006</b>	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
	gs for Fasteners on	USMC USMC-Exp	editionary	5b. GRANT NUMBER	
Fighting Vehicle				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)			5d. PROJECT NU	5d. PROJECT NUMBER	
				5e. TASK NUME	BER
				5f. WORK UNIT	NUMBER
	ZATION NAME(S) AND AD .,Naval Air Systems t River,MD,20670	` '	Shaw Road,	8. PERFORMING REPORT NUMB	G ORGANIZATION ER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release; distributi	on unlimited			
=	otes of Hard Chrome and onsored by SERDP/		g Program Review	Meeting, Ja	nuary 24-26, 2006,
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF				18. NUMBER	19a. NAME OF
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	OF PAGES 53	RESPONSIBLE PERSON

**Report Documentation Page** 

Form Approved OMB No. 0704-0188

# Presented by:

Amy Hilgeman (Sabre Systems, Inc.)

Chemist

**NAVAIR** 

48066 Shaw Road, Bldg 2188

Patuxent River, MD 20670-1906

301-342-0986

amy.leis.ctr@navy.mil



#### **Contributors:**

#### **Bill Nickerson (NAVAIR)**

48066 Shaw Road, Bldg. 2188
Patuxent River, MD 20670-1906
301-342-8864
william.nickerson@navy.mil

#### **Kevin Clark (GDLS)**

14041 Worth Avenue Woodbridge, VA 22192 703-490-7533 clarkk@gdls.com

#### Subra Bettadapur (DRPM-AAA, USMC)

14041 Worth Avenue Woodbridge, VA 22192 703-492-3360 BettadapurSS@EFV.USMC.MIL



#### **USMC-EFV**

- Self-deploying, high-water-speed, armored amphibious vehicle.
- Operated by a crew of 3 Marines.

 Transports up to 17 combat equipped Marines from Naval ships beyond the visual horizon to inland objectives.

http://www.efv.usmc.mil/



# Purpose

 Environmentally "green" program – no hexavalent chrome, no cadmium, etc.

 Original set-up – all bare fasteners contributing to severe galvanic corrosion.

Preliminary screening of alternative fastener

coatings.





# Coatings

#### S4340

- Cadmium ASTM F519, Table II, Treatment B, chromate seal, 0.5 mil (NAVAIR)
- Zinc Nickel AMS 2417F, Type II, chromate seal, 3-5 mil (AMZ)
- Magni 565<sup>TM</sup> Chrome-free coating system combining an inorganic zinc-rich basecoat with an aluminum-rich organic topcoat. (Magni)
- Alumazite™ ZM 40 Heat cured, corrosion inhibiting coating w/ no chromate pigments for carbon steel. (Tiodize)
- Bare



# Coatings (cont.)

- SS470
  - Cadmium
  - Alumazite™ ZY 138 Heat cured, inhibiting coating with no chromate pigments designed for stainless steels and titanium. (Tiodize)
    - Bare
- Ti-6AI-4V
  - **Titanium Anodize** AMS 2488, Type II (Titanium Finishing Co.)
  - Bare



#### **Test Method**

#### Panel Preparation

- AA2519-T87: 3"x6"x0.5" and 3"x8"x0.5"
- Clean Aerowash
- Deoxidize Ridoline<sup>™</sup> 4450
- Pretreat TCP

#### Prime

- MIL-DTL-53022 (Sherwin Williams)
- MIL-PRF-23377, Class C2, Type I (Hentzen)




# **Test Method (cont.)**

- Install Fasteners (55 in. lbs)
  - 1/4" x 1" hex head bolts
    - S4340
    - SS470
    - Ti-6AI-4V
- Sealant Application
  - MIL-PRF-81733D, Type II


  - PR 1775 (PS 1775) Wet Install (53022 or 23377)
  - None (Loctite 242® Threadlocker)
- Topcoat (Scribed)
  - MIL-DTL-64159, Type II
- GM9540P
  - 80 cycles




#### **Painted Corrosion Evaluation**



























# S4340 Wet Install

<u>Coating</u>	<u>Primer</u>	Wet Install
ZnNi	2227	2227
Cd	23377	23377
ZnNi	52022	53022
Cd	53022	
Magni 565™	23377	23377
	53022	53022
Alumazite™ ZM40	23377	23377
	53022	53022
Bare	Bare	53022



## **SS470 Wet Install**

<u>Coating</u>	<u>Primer</u>	<u>Sealant</u>
0.1	23377	23377
Cd	53022	53022
A I: 1 - TM 7\/400	23377	23377
Alumazite™ ZY138	53022	53022
Bare	Bare	53022



## Ti-6Al-4V Wet Install

<u>Coating</u>	<u>Primer</u>	Wet Install
Titanium Anodize	23377	23377
Titanium Anodize	53022	53022
Bare	53022	53022



## **Overall Wet Install**

<u>Fastener</u>	Coating	<u>Primer</u>	Wet Install
S4340	ZnNi		
54340	Cd	23377	23377
SS470	Cd	23311	23377
Ti-6Al-4V	Anodize		
S4340	ZnNi		
34340	Cd	53022	53022
SS470	Cd		
Ti-6Al-4V	Anodize	53022	53022
S4340	Magni 565™	23377	23377
SS470	Alumazite™ ZY 138	23377	23377
SS470	Alumazite™ ZY 138	53022	53022
S4340	Magni 565™	53022	53022



# Overall Wet Install (cont.)

<u>Fastener</u>	<u>Coating</u>	<u>Primer</u>	<u>Wet Install</u>
S4340	Alumazite™ ZM 40	23377	23377
S4340	Alumazite™ ZM 40	53022	53022
Ti-6Al-4V	Bare	Bare	53022
SS470	Bare	Bare	53022
S4340	Bare	Bare	53022



# Overall 81733D

<u>Fastener</u>	<u>Coating</u>	<u>Primer</u>
	ZnNi	53022
S4340	0.4	53022
34340	Cd	23377
	ZnNi	23377
SS470	Cd	23377
Ti-6AI-4V	Anodize	23377
SS470	Alumazite™ ZY138	23377
33470	Alumazite ···· Z 1 136	53022
S4340	Magni 565TM	23377
34340	Magni 565™	53022
Ti-6AI-4V	Anodize	53022
SS470	Cd	Bare
S4340	Alumazita TM 7M 40	23377
34340	Alumazite™ ZM 40	53022



# **Overall PR1775**

<u>Fastener</u>	<u>Coating</u>	<u>Primer</u>
SS470	Cd	53022
S4340	ZnNi	23377
	Cd	23377
Ti-6Al-4V	Anodize	23377
SS470	Cd	23377
S4340	Cd	53022
SS470	Alumazite™ ZY 138	23377
S4340	Magni 565™	53022
S4340	ZnNi	53022
S4340	Magni 565™	23377
Ti-6AI-4V	Anodize	53022
SS470	Alumazite™ ZY 138	53022

<u>Fastener</u>	<u>Coating</u>	<u>Primer</u>
S4340	Alumazite™ ZM 40	23377
S4340	Alumazite™ ZM 40	53022
Ti-6AI-4V	Bare	Bare
SS470	Bare	Bare
S4340	Bare	Bare



## **Overall No Sealant**

<u>Fastener</u>	<u>Coating</u>	<u>Primer</u>
0.40.40	Cd	23377
	ZnNi	53022
S4340		23377
	Cd	53022
Ti-6Al-4V	Anodize	23377
S4340	Magni 565™	53022
SS470	Alumazite™ ZY 138	23377
33470	Alumazile Z i 130	53022
Ti-6Al-4V	Anodize	53022
S4340	Magni 565™	23377

<u>Fastener</u>	<u>Coating</u>	<u>Primer</u>
Ti-6Al-4V	Bare	23377
S4340	Alumazite™ ZM 40	23377
		53022
SS470	Bare	Bare
S4340	Bare	Bare



# Overall S4340

<u>Primer</u>	<u>Sealant</u>
2227	PR1775
23377	23377
53022	81733D
	PR1775
23377	23377
	None
53022	81733D
23377	017330
23377	81733D
F2022	None
53022	53022
53022	PR1775
23377	None
52022	53022
53022	None
	23377 53022 23377 23377 23377 53022 53022



# Overall S4340 (cont.)

<u>Coating</u>	<u>Primer</u>	<u>Sealant</u>
Magni 565™	53022	PR1775
ZnNi		PKIIIS
Magni 565™	23377	81733D
	53022	81733D
	23377	PR1775
		23377
	53022	None
		53022
	23377	None




# Overall S4340 (cont.)

_		
Coating	<u>Primer</u>	<u>Sealant</u>
Alumazite™ ZM40	23377	81733D
	53022	
	23377	PR1775
	53022	
	23377	53022
	53022	23377
	23377	None
	53022	
Bare	Bare	53022
		PR1775
		None




#### S4340 Fasteners






# S4340 Fasteners (cont.)





# S4340 Fasteners (cont.)





## **Overall SS470**

<u>Coating</u>	<u>Primer</u>	<u>Sealant</u>
Cd	53022	PR1775
	23377	23377
	53022	53022
	23377	PR1775
	23377	81733D




# Overall SS470 (cont.)

<u>Primer</u>	<u>Sealant</u>
23377	81733D
53022	
23377	PR1775
53022	53022
23377	23377
23377	None
53022	
Bare	81733D
53022	PR1775
Bare	PR1775
	53022
	None
	23377 53022 23377 53022 23377 53022 Bare 53022




## **SS470 Fasteners**





# SS470 Fasteners (cont.)






# **Overall Ti-6AI-4V**

Primer	Sealant
23377	23377
	PR1775
	None
	81733D
53022	53022
	PR1775
	81733D
	None
23377	None
Bare	53022
Bare	PR1775
	23377 53022 23377 Bare




#### **Ti-6AI-4V Fasteners**





# Ti-6AI-4V Fasteners (cont.)



Bare Bare



#### Conclusions

#### S4340

- Cadmium and Zinc Nickel ranked at the top.
- Magni 565™ ranked in the mid-level.
- Alumazite<sup>™</sup> ZM 40 and Bare were clearly at the bottom.

#### SS470

- Cadmium was a definite first.
- Alumazite™ ZY138 is a better alternative than bare but not close to Cadmium.

#### Ti-6AI-4V

- Titanium anodize is a much better option than bare.



#### Recommendations

- S4340 Zinc Nickel is the best option as cadmium alternative. Further evaluation recommended.
- SS470 Alumazite<sup>™</sup> ZY138 is a better option than the current set-up using bare fasteners.
- Ti-6Al-4V Titanium anodize is a better option than the current set-up using bare fasteners.





- AA2519-T87 High-copper, aluminum armor alloy (sig. weight reduction vs. 5083)
- S4340 Ni-Cr-Mo high-strength steel
- SS470 Work-hardened 316 stainless steel alloy
- Ti-6Al-4V Titanium alloy, 6% aluminum and 4% vanadium.



- Aerowash Mildly alkaline, all-purpose maintenance cleaner (Henkel)
- Ridoline<sup>™</sup> 4450 Phosphate-free, dilute citric/acetic acid deoxidizer (Henkel)
- TCP Trivalent chromium conversion coating for aluminum and its alloys (NAVAIR)



- MIL-DTL-53022 Solvent-borne, nonchromated epoxy primer (Sherwin Williams)
- MIL-PRF-23377, Class C2, Type I High-solids, solvent-borne, chromated epoxy primer (Hentzen)
- MIL-DTL-64159, Type II Waterreducible, CARC topcoat (Hentzen)



- MIL-PRF-81733D, Type II Twocomponent, room temp curable, polysulfide sealant with a hexavalent chrome inhibitor to prevent corrosion.
- PR 1775 Two-component room temp curable, polysulfide sealant with a nonchromate inhibitor to prevent corrosion.



- GM9540P Accelerated, cyclic corrosion test. Three stages repeated for each cycle:
  - 8 hr ambient with 4 salt mist applications every 90 min (40%-50% RH, 25C)
  - 8 hr humidity (100% RH, 49C)
  - 8 hr dry (<30% RH, 60C)




- Zinc Nickel Plating performed in accordance with AMS 2417F Type II at a thickness of 0.0003" - 0.0005" - post-treated with hexavalent chrome (AMZ)
- Cadmium Plating performed in accordance with ASTM F519, Table II, Treatment B, chromate seal, 0.5 mil (NAVAIR)
- Magni 565<sup>™</sup> Chrome-free duplex fastener coating system that combines an inorganic zinc-rich basecoat with an aluminum-rich organic topcoat.



- Alumazite<sup>™</sup> ZM40 Heat cured, corrosion inhibiting coating with no chromate pigments for carbon steel (Tiodize)
- Alumazite<sup>™</sup> ZY138 Heat cured inihibiting coating with no chromate pigments designed for stainless steels and titanium(Tiodize)
- Titanium Anodize Anodized in accordance with AMS 2488, Type II (Titanium Finishing Company)



### **S4340 Fasteners**




ZnNi

53022



#### **S4340 Fasteners**






#### S4340 Fasteners

Alumazite<sup>™</sup> ZM40 53022


Alumazite<sup>™</sup> ZM40 23377



Bare Bare



## **SS470 Fasteners**






## **SS470 Fasteners**





## **Ti-6AI-4V Fasteners**





## **Ti-6AI-4V Fasteners**

